



ENCLOSURE FOR 22MM PROGRAM PLASTIC VERSION
2 COMMAND POSITIONS GRAY TOP PART

Enclosure:

Material / of the housing

plastic

Color / of the top part of housing

grey

Actuator:

Material / of the activation element

plastic

General technical details:

Product designation

empty enclosure for commanding and signaling devices

Design of the product / with coat of paint

No

Number of control points

2

Supply status / pre-wired on terminal strip

No

Supply status / as a kit

No

Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750

S

Item designation / according to DIN EN 61346-2

U

Type of fixing/fixation / for switching elements, socket fixing and accessories

floor mounting

Product component

- stand/pedestal
- protective collar

No

No

Auxiliary Contacts:

Number of NC contacts / for auxiliary contact		0
Number of NO contacts / for auxiliary contact		0
Number of change-over switches / for auxiliary contact		0

Installation/mounting/dimensions:

Type of fixing/fixation		screw fixing
Shape / of the installation hole		round
Mounting diameter	mm	22
Width	mm	85
Height	mm	114
Depth	mm	64

Ambient conditions:

Protection class IP		IP65
Ambient temperature		
• during the operating phase	°C	-25 ... 70
Climatic class / according to DIN 50017		KTW24

Further information:**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

Global Industry Mall (Online ordering system)


<http://www.siemens.com/industrial-controls/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SB3802-0AA3/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB3802-0AA3



last change:

Aug 16, 2010