



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool		
							mt.	Type	Kg.
C707	4x2	4 x 2 x 24 (0,22 mm ²)	1x0,50 CCA	0,9		5,0	305		

Characteristics:

Conductors: stiff wire in CCA
 Cond. insulation: PE
 Pair colours: White/blue-Blue,
 White/orange-Orange,
 White/green-Green,
 White/brown-Brown
 Total tape: transparent Polyester (Pet)
 External Sheath: PVC
 Sheath colour: Grey

Product Description

U.T.P. (Unshielded Twisted Pairs) cable cat. 5e (enhanced) for Local Area Network. LAN cable for fixed installations and for realization of assembled cables with **RJ 45 8 Pin** connectors according with standards: **EIA/TIA 568**.
 Advised for Broadcast application and Network installation in: EDP centres, cinematographic studios, TV directions, Recording rooms, Theatres, public buildings and sport facilities, industrial environments and control centres in general.
 This cable is suitable for connection and supply of Cat. 5e equipments, Racks and Hub-LAN.

Connectors:

RJ 45 8 Pin connector

Conductor Resistance Ω/Km ± 5%	Impedance Ω ± 15% 1 ÷ 100 MHz	Max Rated Voltage AC - V
110	100	49
		Operative Temperature °C -15 / +70



- CCA
- PE
- PVC

Descrizione Prodotto

U.T.P. (Unshielded Twisted Pairs) di cat. 5e (enhanced) per cablaggio di reti locali (Local Area Network).
 Cavo LAN per installazione fissa e per la realizzazione di cavi assemblati con connettore **RJ 45 8 Pin** secondo le norme: **EIA/TIA 568**.
 Consigliato per applicazioni Broadcast ed installazioni Network in: centri EDP, studi cinematografici, regie televisive, sale di registrazione, teatri, edifici pubblici ed impianti sportivi, ambienti industriali e centri di controllo in genere.
 Questo cavo è adatto al collegamento di Armadi Racks, Hub-LAN ed apparecchi di Cat. 5e.

U.T.P. cables cat. 5e



tasker® Code	Cond. number	Nominal section AWG	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool		
							mt.	Type	Kg.
C708	4x2	4 x 2 x 26 (0,14 mm ²)	7x0,16 CCA	0,9		5,0	305		

Characteristics:

Conductors: stranded in CCA
 Cond. insulation: PE
 Pair colours: White/blue-Blue,
 White/orange-Orange,
 White/green-Green,
 White/brown-Brown
 Total tape: transparent Polyester (Pet)
 External Sheath: PVC
 Sheath colour: Grey

Product Description

U.T.P. (Unshielded Twisted Pairs) cable cat. 5e (enhanced) for Local Area Network. LAN cable for mobile installations and for realization of assembled cables with **RJ 45 8 Pin** connectors according with standards: **EIA/TIA 568**.
 Advised for Broadcast application and Network installation in: EDP centres, cinematographic studios, TV directions, Recording rooms, Theatres, public buildings and sport facilities, industrial environments and control centres in general.
 This cable is suitable for connection and supply of Cat. 5e equipments, Racks and Hub-LAN.

Connectors:

RJ 45 8 Pin connector

Conductor Resistance Ω/Km ± 5%	Impedance Ω ± 15% 1 ÷ 100 MHz	Max Rated Voltage AC - V
170	100	49
		Operative Temperature °C -15 / +70



- CCA
- PE
- PVC

Descrizione Prodotto

U.T.P. (Unshielded Twisted Pairs) di cat. 5e (enhanced) per cablaggio di reti locali (Local Area Network).
 Cavo LAN per installazione mobile e per la realizzazione di cavi assemblati con connettore **RJ 45 8 Pin** secondo le norme: **EIA/TIA 568**.
 Consigliato per applicazioni Broadcast ed installazioni Network in: centri EDP, studi cinematografici, regie televisive, sale di registrazione, teatri, edifici pubblici ed impianti sportivi, ambienti industriali e centri di controllo in genere.
 Questo cavo è adatto al collegamento di Armadi Racks, Hub-LAN ed apparecchi di Cat. 5e.