

7929A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable



For more Information
please call
1-800-Belden1



Description

24 AWG Bonded-Pairs solid bare copper conductors, polyolefin insulation, overall Beldfoil® shield (100% coverage), industrial grade sunlight- and oil-resistant PVC jacket, drain wire, rip cord. Sequential marking at two foot intervals

Suitable Applications (Overall):

Suitable Applications

Industrial Ethernet Cable, Harsh Environments, 200MHz Category 5e, Industrial Ethernet, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, CMX - Outdoor, RJ-45 Compatible

Physical Characteristics (Overall):

Conductor:

AWG

# Pairs	AWG	Stranding	Conductor Material
4.000	24	Solid	BC - Bare Copper

Insulation:

Insulation Material

Insulation Material	Wall Thickness (in.)
PO - Polyolefin	0.010

Outer Shield:

Outer Shield Material

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

Outer Jacket:

Outer Jacket Material

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Ripcord

No

Overall Cabling:

Overall Nominal Diameter:

.265 in.

Pair:

Pair Color Code Chart

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall):

Operating Temperature Range -40°C To +75°C

Installation Temperature Range -25°C To +75°C

Bulk Cable Weight: 32 lbs/1000 ft.

7929A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

Max. Recommended Pulling Tension:	35 lbs.
Min. Bend Radius (Install)/Minor Axis:	0.500 in.

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards:

NEC/(UL) Specification	CMR, CMX-Outdoor, UL444
CEC/C(UL) Specification	CMR
IEC Specification	11801 Category 5
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	01/01/2004
PMSHA Specification	P-07-KA060003
TIA/EIA Specification	568-B.2 Category 5e
Other Specification	NEMA WC-63.1 Category 5e, UL verified to Category 5e

Flame Test:

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

Suitability:

Suitability - Outdoor	Yes
Sunlight Resistance	Yes
Oil Resistance	Yes

Plenum/Non-Plenum:

Plenum (Y/N)	No
Plenum Number	1533P
Non-Plenum Number	1533R

Electrical Characteristics (Overall):

Nom. Mutual Capacitance

Capacitance (pF/ft)
15.000

Nominal Velocity of Propagation

VP (%)
70

Maximum Capacitance Unbalance (pF/100 m) 330

Maximum Delay

Delay (ns/100 m)
538 @ 100MHz

Max. Delay Skew

Delay Skew (ns/100 m)
45

Maximum Conductor DC Resistance

DCR @ 20°C (Ohm/100 m)
9.380

Max. Operating Voltage - UL

Voltage
300 V RMS

Maximum DCR Unbalanced

DCR Unbalance @ 20°C (%)
3.000

Electrical Characteristics-Premise (Overall):

7929A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

Premise Cable Electrical Table 1

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)	Min. SRL (dB)
1	2.000	65.300	62.300	63.000	60.000	20.000	23
4	4.100	56.300	53.300	51.000	49.000	23.000	23.000
8	5.800	51.800	48.800	46.000	43.000	24.500	24.500
10	6.500	50.300	47.300	43.000	41.000	25.000	25.000
16	8.200	47.300	44.300	39.000	36.000	25.000	25.000
20	9.300	45.800	42.800	36.500	33.500	25.000	25.000
25	10.400	44.300	41.300	33.900	30.900	24.300	24.300
31.250	11.700	42.900	39.900	31.000	28.000	23.600	23.600
62.500	17.000	38.400	35.400	22.000	19.000	21.500	21.500
100	22.000	35.300	32.300	14.000	11.000	20.100	20.100
200	32.400		27.800		1.000		15.000

Premise Cable Electrical Table 2

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.800	60.800
4	100 ± 15	100 ± 15	51.700	48.700
8	100 ± 15	100 ± 15	45.700	42.700
10	100 ± 15	100 ± 15	43.800	40.800
16	100 ± 15	100 ± 15	39.700	36.700
20	100 ± 15	100 ± 15	37.700	34.700
25	100 ± 15	100 ± 15	35.800	32.800
31.250	100 ± 15	100 ± 15	33.900	30.900
62.500	100 ± 15	100 ± 15	27.800	24.800
100	100 ± 15	100 ± 15	23.800	20.800
200	100 ± 25			14.700

Notes (Overall):

Notes US Patent #'s 5, 606, 151; 5, 734, 126. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581.

PUT UPS AND COLORS:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7929A 0061000	1,000 FT	37.000 LB	BLUE, LIGHT	C	4 PR #24 PP FS PVC BLULT
7929A 0101000	1,000 FT	37.000 LB	BLACK	C	4 PR #24 PP FS PVC BLK
7929A 0102000	2,000 FT	72.000 LB	BLACK	C	4 PR #24 PP FS PVC BLK

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 7 Revision Date: 05-14-2007

© 2008 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS). EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or

7929A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.