



## 88226014-6 min 12 h



### Relay output

- ✓ Mono-voltage
- ✓ 1 timed changeover and 1 instantaneous contact
- ✓ Elapsed time can be saved mechanically in the event of a break in supply
- ✓ Progress of cycle displayed
- ✓ Housing 48 x 48 mm
- ✓ Connection by screw-terminal base or 8-pin base

### Precision limit error

Repetition accuracy	± 1.5% (± 4%/6 s)
Selection precision	See "timing ranges" table for scale graduation
Reset time	0.20 s

### Timed two-pole

Instantaneous single pole	1
Thermal rating	6,3 A
Rating (cos φ = 0.41) 10 <sup>4</sup> operations	5 A - 230 V

### Absorbed power-motor


Voltage variation at maximum temperature of 55 °C according to IEC 255 100	24 V +10% - 42 V -15% 48 V +10% - 110 V -20% 127 V 0% - 220 V -20% 240 V 0%
--	--

Operator factor	100%
Temperature limits use (°C)	-10→+55
Temperature limits stored (°C)	-20→70
Environmental protection Tropicalised to IEC 68-2-10	✓
Vibration withstand on 3 axes (Veritas standard)	4 G - 55 Hz
Dielectric test voltage according to IEC 255 5 or VDE 0435	1000 V - Un ≤ 60 V 2000 V - Un > 60 V
Insulation according to standard VDE 0110 group C	380 V AC - 440 V DC
Protection Housing	IP 40
Degree of terminal protection	IP 10
Conformity to standards NFC 45250 - VDE 0110 - 0435 - 0660 or ICE 529	✓
Connection: Screw/saddle	✓
Terminal capacity Single-wire 1 or 2 leads Multi-wire	0,75 - 2,5 mm <sup>2</sup>
Terminal capacity Multi-wire 1 or 2 leads	0,5 - 1 mm <sup>2</sup>
Mounting: Base mounting on 8-pin socket	✓
Weight (g)	185

### Accessories


Accessories	Code
Solder tag connector 8-pin	25622301
8-pin connector base	25622128
Invertor for DC supply 24-48 V	84861501
Invertor for DC supply 110-127 V	84861503

### Curves :



### Function

### Curves :




**Function**

**Curves :**




**Function**


**: Function 2**




**: Function 3**



**: Function 4**




**: 88 226 0**




N°	Legend
A1 - A2	Supply
15 - 16 - 18	Timed contact
23 - 24	Instantaneous contact

**: 88 226 0**



N° 2-3	Legend
A1-A2	Supply
15-16-18	Timed contact
23-24	Instantaneous contact


**: 88 226 5**



N°	Legend
----	--------

2 - 7                      Supply  
8 - 5 - 6                Timed contact  
3 - 1                      Instantaneous contact

**: 88 226 5**



N°	Legend
2-7	Supply
8-5-6	Timed contact
3-1	Instantaneous contact