

MNX ABS 95/75 HG



Sample photo

Order symbol: ABS 95/75 HG
Product nbr: 6081332
Description: Enclosure, ABS
Remarks: Grey cover

EAN: 6418074054722
EI. number:
Finland: 3421382
Denmark: 8212023990
Sweden: 6081332
Norway:

Including: Base with PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

| Dimensions: | | Length | Width | Height | Rating: |
|-------------------------------|--|-----------------------------------|-------|--------|--|
| mm: | | 100 | 100 | 75 | Ingress Protection (EN 60529): IP 66/67 |
| inch: | | 3.9 | 3.9 | 3.0 | Impact Resistance (EN 62262): IK 07 |
| Materials: | | | | | Electrical insulation: Totally insulated |
| Material: | | ABS | | | Halogen free (DIN/VDE 0472, Part 815): Yes |
| Base colour: | | RAL 7035 | | | Flammability Rating (UL 746 C 5): UL 94 HB |
| Cover colour: | | RAL 7035 | | | Glow Wire Test (IEC 695-2-1) °C: 650 |
| Cover screws material: | | Polyamide | | | NEMA Class: NEMA 1, 4, 4X, 6, 12, 13 |
| Cover screws colour: | | Grey | | | |
| Gasket material: | | Polyurethane | | | |
| Temperatures: | | | | | Certificates: |
| Short term: | | -40 ... 80 °C | | | Fimko |
| Continuous: | | -40 ... 60 °C | | | Europe EN 62208: 2003 |
| Short term: | | -40 ... 175 °F | | | Gost R |
| Continuous: | | -40 ... 140 °F | | | |
| Accessories: | | | | | |
| MIV 95 | | Mounting plate (Galvanized steel) | | | |
| MIN 8 | | DIN-15 Mounting rail | | | |
| B-3 | | DIN-35 Mounting rail | | | |
| FP 22046 | | Wall fastening lug (4 pcs) | | | |

