



BN 1206

Vis à tête cylindrique

à six pans creux avec tête extrêmement basse

Acier ~010.9

noir

i Les vis selon la spécification présente ont du fait de la géométrie de la tête des capacités de charge réduites selon ISO 898-1.

Article#	d ₁	d ₂	k max.	a min.	a max.	s	t max.	L
3555966	M2	4	1,27	-	1,2	1,3	1,2	4
3555967								5
3555968								6
3555969								8
3555970								10
3555971	M2,5	5	1,37	-	1,4	1,3	1,5	4
3555972								5
3555973								6
3555976								8
3555978								10
3555979								12
3555981	M3	6	1,37	-	1,5	1,5	2	5
3555982								6
3555983								8
3555984								10
3555985								12
3555986								16
1415549	M4	8	1,5	1,4	2,1	2	2,5	6
1415557								8
1415565								10
3055501								12
3646034								16
3646035								20

Article#	d ₁	d ₂	k max.	a min.	a max.	s	t max.	L
1383116	M5	9	1,5	1,4	2,2	3	3	6
1415573								8
1415581								10
1415603								12
1415611								16
1415638								20
3055503								25
3646036								30
3646037								35
3646038								40
1383078	M6	10	1,5	1,4	2,4	3	4	6
1415646								8
1415654								10
1415662								12
1415670								16
1415689								20
1415697								25
3055505								30
3646039								35
3646040								40
3646041								50
1415700	M8	13	1,5	2	3,2	4	5	8
1415719								10
1415727								12
1415735								16
1415743								20
1415751								25
1415778								30
3646042								35
3055506								40
3646043								45
3646044								50
1415786	M10	16	1,5	2	3,5	5	6	10
1415794								12
1415808								16
1415816								20
1415824								25
1415832								30
3646045								35
3055507								40