



- 1.CABLE:NO UL 14C+1.<<(28AWG,7/0.12mm±0.008)>>x14C
SHIELD:DRAIN WIRE+AL/MY COVERAGE
JACKET:PVC,COMPLIANCE ROHS,COLOR:BEIGE,Ø.D:6mm±0.2mm
- 2.CONNECTOR:2 PCS HDD15 PIN MALE SOLDER TYPE CONNECTOR
SHELL:NICKEL PLATED
- 3.HOOD:PVC MOLDED TYPE WITH AL-FOIL SHIELDED ON INNER
MOLD INJECTION OUTER MOLD WITH THUMB SCREW#4-40UNC
HOOD COLOR IS BEIGE,COMPLIANCE ROHS
- 4.Fulfill ROHS Guideline
- 5.ELECTRONIC TEST: 100% OPEN SHORT+MISS WIRE TEST

DRAWING

HDD15PIN PLUG(P1)	WIRE	HDD15PIN PLUG(P2)
1	————	1
2	————	2
3	————	3
4	————	4
5	————	5
6	————	6
7	————	7
8	————	8
10	————	10
11	————	11
12	————	12
13	————	13
14	————	14
15	————	15
SHELL	D.W	SHELL

PART NO	C-15WHD/1,8	SHEET NO	1	THIRD ANGLE PROJECTION			
TITLE: HDD15 PIN PLUG TO HDD15 PIN PLUG BEIGE COLOR,L:1.8M					SCALE	N.T.S	DRAWN BY & DATE
					SIZE	A4	CHECKED BY & DATE
DWN NO					UNIT	mm	INCH
				APPROVED BY & DATE			

