



1. CABLE: UL2725, 28AWG(7/0.12mm) x 1 PAIRS
+ 24AWG(7/0.2mm) x 2C, TIN COPPER
INSULATOR: PP FOR 28AWG & PVC 24AWG
SHIELD: AL-FOLI + DRAIN WIRE + BRAID
JACKET: PVC, COLOR: GREY, D.D: 4.8mm ± 0.2mm
2. CONNECTOR: 1 PCS USB A SOLDER TYPE MALE
COLOR: WHITE COLOR
SHELL: NICKEL PLATED
3. CONNECTOR: 1 PCS USB A SOLDER TYPE FEMALE
SHELL: NICKEL PLATED
4. HOOD: MOLDED GREY COLOR
5. Fulfill ROHS Guideline
6. ELECTRONIC TEST: 100% OPEN SHORT + MISS WIRE TEST

WIRE LIST

P1		P2	
USB A MALE	WIRE COLOR	USB A FEMALE	AWG
1	RED	1	24AWG
2	WHITE	2	1 PAIRS (28AWG)
3	GREEN	3	24AWG
4	BLACK	4	
	SHELL DRAIN	4	SHELL

PART NO	CAB-USBAAF-1.8	SHEET NO	1	THIRD ANGLE PROJECTION
TITLE:	USB A MALE TO USB A FEMALE			
	L1.8M, UL2725 CABLE, GREY COLOR			
DWN NO	D-CAB-USBAAF-1.8	SCALE	N.T.S	DRAWN BY & DATE
		SIZE	A4	CHECKED BY & DATE
		UNIT		APPROVED BY & DATE
		<input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH		

