



Art No. CAB1101

Toslink Audio Cable M/M, Metal, 1,5M

1500±30mm





Our Toslink Cable is Gold Plated for optimized connectivity, longevity and signal strength. The Fiber-Optic tip is precision-polished for maximum signal transfer. Use our premium Toslink Cable to transfer 100% Digital Optical Audio from Dolby Digital Receivers, Digital

Signal Processors, DivX Players, DVD players, CD players, DSS receivers, Sony Playstation 2 & 3, XBox and much more.

Technological Parameter

Fiber Specification ltem Spec. ltem Fiber Diameter Center 1mm Material Outside Diameter 2.2mm Core Construct mm/No. Fiber Material PMMA O.D. mm Application Lighwave 650nm Outer Material Attenuation ≤ 0.18 dB/m Coating O.D. mm **Bend Radius** 5Xcore Diameter Color $-15^{\circ} \sim 80^{\circ}$ Used Temperature Outer Material Sheath Connection Loss ≤0.5dB O.D. mm Dutter PVC Diameter 5.0 + 0.2Color

Packaging Information:

L	Т	Q'ty	Carton Dimension
150cm	3cm	20pcs	420x340x270 mm





Spec.

0.98

PE

2.2

Black

 5.0 ± 0.2

PVC

Black

Plastic Fiber

0.98mm x 1



