



Type: 57668
Designation:..... **Universal Charger**

Systems to charge: **Ni-MH**
Cell sizes:..... AAA, AA,C,D,9V
Cell Configurations:..... AAA, AA, 2 / 4 pcs.
C/D: 2 / 4pcs
9V: 1pcs

Dimensions:	Charger:	AC/DC-Adapter:
Lenght:.....	166mm	68mm
Widht:.....	95mm	29mm
Height:.....	54.8mm	43mm
Weight:.....	241g	

Charging methods:	AC adapter 12V 600mA	Maintenance Charge:
AA:.....	Current: 380 mA ± 10%	Current: 0mA
AAA:.....	Current: 150 mA ±10%	Current: 0mA
C/D	Current:380mA ±10%	Current: 0mA
9V	Current:34mA ±10%	Current: 0mA

Housing:	Indications: LED display
Housing Material:..... ABS V-0	AAA, AA,cell mix:..... LED solid on = Fast Charge LED off = fully charged or no battery
Casing color:..... Black	

Protective Functions:	Power:
	Primary:..... 100-240 VAC 50/60 Hz
	Secondary:..... 2.8V

Cut off criteria:
Ni-MH standard cells:... Timer:Backup timer 8 hours

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries