Honeywell



Representative photograph, actual product appearance may vary.

Due to regional agency approval requirements, some products may not be available in your area. Please contact your regional Honeywell office regarding your product of choice.

GLDB01B

Global Limit Switches Series GLS: Top Plunger, 1NC 1NO SPDT Snap Action, PG13.5

Features

- Designed to IEC standard for world-wide applications
- UL, CSA, and CE
- International conduit sizes
- Direct PLC interface compatible (two circuit)
- Modular construction reduces maintenance parts costs
- Designed for ease of installation
- Variety of basic switch versions
- · Wide choice of actuators

Typical Applications

- Machine tools: metal fabrication equipment, presses, transfer lines and special machinery
- Material handling equipment: conveyors, elevators, cranes, and hoists
- Packaging machinery and process equipment
- Textile machinery
- Construction machinery and equipment, vehicles and lift trucks

Description

The GLS series limit switches are specifically designed for worldwide applications and are supported by Honeywell global resources for sale and after sale service.



GLDB01B

Global Limit Switches Series GLS: Top Plunger, 1NC 1NO SPDT Snap Action, PG13.5

| Global Limit Switches Series CES. Top Hanger, The The St E1 Shap Action, 1 013.5 | |
|--|--|
| Product Specifications | |
| Availability | Global |
| Product Type | EN50041/47 Global Limit Switch |
| Actuator | Top Plunger |
| Lever Style | None |
| Circuitry | 1NC 1NO SPDT Snap Action |
| Ampere Rating | 10 A (Thermal) |
| Supply Voltage | 600 Vac and 250 Vdc max. |
| Housing Material | Plastic |
| Termination Type | PG13.5 |
| Housing Type | EN 50047 |
| Series Name | GLS Series |
| Shock | 50 g per IEC 68-2-27c (w/o Actuator) |
| Vibration | 10 g per IEC 68-2-6 (w/o Actuator) |
| Sealing | NEMA 1, 12, 13 IP66 |
| Approvals | UL, CSA, CE |
| CSA File # | LR94369-3 |
| UL File # | E37138 & E157416 |
| Mechanical Life | 15 million |
| Operating Temperature Range | -25 °C to 85 °C [-13 °F to 185 °F] |
| Agency Approvals and Standards | IEC 947-5-1, EN60947-5-1, UL508, UL746-C |
| UNSPSC Code | 302119 |
| UNSPSC Commodity | 302119 Switches and controls and relays |
| Sealed | Industrial |



GLDB01B

Global Limit Switches Series GLS: Top Plunger, 1NC 1NO SPDT Snap Action, PG13.5

A WARNING

PERSONAL INJURY

DO NOT USE these products as safety or emergency stop devices, or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

A WARNING

MISUSE OF DOCUMENTATION

- The information presented in this product sheet (or catalog) is for reference only. DO NOT USE this document as product installation information.
- Complete installation, operation and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

© Copyright Honeywell Inc.1998-2002 All rights reserved.