


Product Description

Benefits see SKINTOP® MS



Application range

- With reducing seal insert, to seal cables with smaller outer diameters.

Benefits

- Benefits see SKINTOP® MS

Design

- PG connection thread

Note

- For suitable accessories see SKINTOP® accessories PG
- Counter nut to be used SKINDICHT® SM



Technical Data

Caution

Installation dimensions and tightening torques see Appendix T21

Material

Body: Nickel plated brass Insert: Polyamide Seal: CR O-ring: NBR

Degree of protection

IP 68 - 5 bar

Range of temperature

-30°C up to +100°C

Article List

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINTOP® MSR						
52015770	MSR 7	2 - 5	14	25.0	5.0	100
52015780	MSR 9	2 - 6	17	29.0	6.0	100
52015790	MSR 11	3 - 7	20	32.0	6.0	50
52015800	MSR 13,5	4 - 9	22	34.0	6.5	50
52015810	MSR 16	6 - 13	24	35.0	6.5	50
52015820	MSR 21	8 - 16	30	40.0	7.0	25
52015830	MSR 29	10,5 - 20	40	48.0	8.0	25
52015831	MSR 36	19 - 26	50	62.0	15.0	10
52015832	MSR 42	24 - 31	57	62.0	15.0	5
52015833	MSR 48	28 - 35	64	62.0	15.0	5
SKINTOP® MSR-XL						
52115770	MSR 7	2 - 5	14	32.0	12.0	100
52115780	MSR 9	2 - 6	17	35.0	12.0	100
52115790	MSR 11	3 - 7	20	38.0	12.0	50
52115800	MSR 13,5	4 - 9	22	39,5	12.0	50
52115810	MSR 16	6 - 13	24	40,5	12.0	50
52115820	MSR 21	8 - 16	30	45.0	12.0	25
52115830	MSR 29	10,5 - 20	40	52.0	15.0	25

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.