



CONSTRUCTION:

[(1/0.57)*4P]BC+”+”PE CROSS

CONSTRUCTION DESCRIPTION :

1. CONDUCTOR: 1/0.57 ± 0.005BC
ID: 0.98 ± 0.02mm
MATERIAL: HDPE (210)
2. CROSS: 4.3 ± 0.1mm MATERIAL: HDPE (210)
3. STANDING PITCH: 100 ± 10mm STANDING DIRECTION: RIGHT
4. FILLER: 500D NYLON PLASTIC
5. OUTER DIAMETER: 6.0 ± 0.2mm
MATERIAL: 45P PVC (520-6919-45)
COLOR: OFFWHITE

6. MAKING:

NETWORK SYSTEMS CABLE UTP ANSI TIA/EIA 568-B.2-1 23AWG (4PR) OR
ISO/IEC11801 VERIFIED CAT 6 1M (2M,, 15M,, 305M)

7. PACKING: 305M/R

CORE COLOR :

blue/white&blue
brown/white&brown
orang/white&orang
green/white&green

REMAKE:

1. THE ID AND OD OF THE WIRE MUST BE EXACT, CAN NOT REDUCE THE CENTRE.
2. ALL OF THE MATERIAL FOR THE CABLE ARE COMPLIANT WITH RoHS STANDARD.
3. SPARK TEST OF THE CORE'S VOTAGE: AC/2.5KV
4. THICKNESS OF COAT BY EQUALITY: 0.5mm, THE LEAST THICKNESS: 0.45mm
5. THICKNESS OF CORE BY EQUALITY: 0.2mm, THE LEAST THICKNESS: 0.18mm



VCOM International Ltd.

DRING NO.		PRODUCT NO.		TITLE:						
PK-360A				CAT6 UTP 0.57BC						
APPROVED BY	CHECKED BY	DRAWN BY	CUSTOMER	PAGE	UNIT	SCALE		A/0		2013-02-18
		xiang		1 of 1	mm			REV	RESRIPTION	DATE