

6000 SP Splash Resistant Rocker Switches

16A 250Vac



Key Features

- Ratings up to 20A, 277Vac
- Positive switch action
- Distinctive styling
- Illuminated & nonilluminated
- Single pole
- Panel cut out: 30.1 x 11.1mm

Approvals and specifications


European 16(4)A 250Vac T125, 10A 400Vac T125

UL = 20A 277Vac, 1 1/2HP 250Vac 1HP 125Vac
CSA = 20A 277Vac, 1HP 125Vac, 1/2HP 125Vac

3mm contact gap with Positive Break switching.
Call factory for IP details.

Terminal	Function	Rocker	Body	Body Colour	Rocker Colour	Lamp Voltage	
<p>C</p> <p>6.3 x 0.8</p> <p>9.7</p>	<p>6000</p> <p>ON - OFF</p>	<p>A</p> <p>Softline Matt</p> <p>A</p> <p>Softline Matt</p> <p>P</p> <p>Lit window Matt</p>	<p>L</p> <p>Panel cut-out ** Bezel</p> <p>30.0/30.1</p> <p>11.0/11.1</p> <p>31.5</p> <p>14.0</p> <p>R2.0</p> <p>Cut-outs must be punched in the direction of insertion</p>	<p>B</p> <p>Black</p> <p>W</p> <p>White</p>	<p>Lit (DP)</p> <p>A</p> <p>Amber</p>	Blank	
	<p>6001</p> <p>ON - OFF (momentary ON)</p>				<p>C</p> <p>Clear</p>	2	125V Neon
	<p>6002</p> <p>ON - OFF (momentary OFF)</p>				<p>G</p> <p>Green</p>	3	250V Neon
	<p>6003</p> <p>ON - OFF Lit</p>				<p>R</p> <p>Red</p>	5	12Vdc LED (P Rocker)
	<p>6008</p> <p>ON - OFF Lit (Unswitched neutral)</p>				<p>Lit (DP)</p> <p>B</p> <p>Black</p>	6	24Vdc LED (P Rocker)
	<p>6009</p> <p>ON - OFF (momentary ON) Lit (Unswitched neutral)</p>				<p>R</p> <p>Red</p>	7	12V Filament
	<p>6010</p> <p>ON - ON</p>				<p>W</p> <p>White</p>	8	24Vdc Filament
	<p>6011</p> <p>ON - ON (momentary 1 side)</p>						

Dimensions




Panel thickness
L 0.75 to 2.5mm
** For cut-out details on momentary switches call sales

Integral Splash Resistance



Current carrying parts are protected from moisture. Droplets which may enter the switch are channelled out through ports in the switch body. For IP65 see options below

Legend	Legend Colour	Options
Blank	Blank	G74 Protective Cover
1223	B Black	<p>Finish Matt is standard.</p> <p>Colour Call sales for custom colours. A full range is available for large orders.</p> <p>Legend printing Select from the examples or call sales for custom legends.</p> <p>Lamp voltage Call sales for details.</p> <p>Protective cover A snap on cover is available (add G after body code), this reduces panel thickness by 2mm.</p>  <p>Panel sealing washer W46 is available, this reduces panel thickness by 1.2mm.</p> <p>Covers are not suitable for momentary types. For all options call the factory</p>
	W White	

Examples



☐ C6000AL - - -



☐ C6000AL - - -



☐ C6010AL - - -



☐ C6003AL - - -



☐ C6003PL - - -



☐ C6030AL - - -