

Video/Audio cables



Applications:
Extra flex cable with separately shielded and insulated cores for assembled cables. Suitable to connect mini-Jack audio/video or Mini-DIN connectors 4-7-8 poles.

Characteristics:
 Conductors: O.F.C. tinned copper
 Cond. Insulation: PVC
 Core colours: Yellow, Grey, Red
 Shields: Spiral covering 100% O.F.C. tinned copper PVC
 Inner Sheaths: PVC
 Inner Sheath colours: Blue-night
 External Sheath: PVC
 Sheath colour: Blue-night



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
TSK 1053	3	3 x 0,08 (28 AWG)	12x0,10	0,9	2,0	4,7	100	B	3,5

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
210	65	230
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70



Applications:
Flexible cable composed of: 3 separately shielded and insulated cores and 2 insulated cores for assembled cables. Suitable to connect 6 poles DIN 45322 plug.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: 3 PE
 +2 PVC
 Core colours: 3 Transparent
 +2 Yellow, White
 Shields: Spiral covering 100% O.F.C. red copper PVC
 Inner Sheaths: PVC
 Inner Sheath colours: Red, Blue, Yellow
 External Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C125	3 +2	3 x 0,12 +2 x 0,12 (26 AWG)	16x0,10	1,0	2,1	6,0	100	B	6,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
140 140		270
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70

Notes: