

## Spiral shielded cables



**Applications:**  
Flexible cables with separately shielded and insulated cores for sound reproduction and electronics.

**Characteristics:**  
 Conductors: O.F.C. red copper  
 Cond. Insulation: PVC  
 Core colours: Blue, White, Red, Yellow, Green, Blue, Grey, Orange, Pink, Brown, Light-Blue, Violet  
 Shields: Spiral covering 100%  
 O.F.C. red copper  
 Inner sheaths: PVC – red colour  
 Sheath: PVC  
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C122	4	4 x 0,14 (26 AWG)	18x0,10	1,1	2,2	8,0	100	B	9,5
C120	6	6 x 0,14 (26 AWG)	18x0,10	1,1	2,2	9,3	100	B	11,6
C201	8	8 x 0,14 (26 AWG)	18x0,10	1,1	2,2	10,0	100	B	16,3
C163	12	12 x 0,14 (26 AWG)	18x0,10	1,1	2,2	14,0	100	B	20,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
130	80	340
130	80	340
130	80	340
130	80	340
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70



**Applications:**  
Flexible cable for sound reproduction and electronics.

**Characteristics:**  
 Conductors: O.F.C. red copper  
 Cond. Insulation: PVC  
 Core colours: Red, Blue, Yellow, Brown, White, Grey, Black  
 Shield: Spiral covering 100%  
 O.F.C. red copper  
 Sheath: PVC  
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C182	7	7 x 0,25 (23 AWG)	8x0,20	1,5	6,3	100	B	6,0

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
75	120	210
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70