

| TECHNICAL DATA SHEET | code | YE00906 |
|-----------------------------|---------|------------|
| | version | 2 |
| EIB cable 4x0.8B PE FS FRNC | date | 2009-03-10 |
| | page | 1/2 |

APPLICATION

EIB cable for building management.

CONSTRUCTION



1. Conductor

Diameter of conductor 0.8 mm (0.5mm2) Material solid bare copper

2. Insulation

Material PE

 $1.60 \pm 0.05 \text{ mm}$ Diameter over insulation

Wallthickness 0.4 mm

3. Overall Cabling

four wire into a quad Colour code white-red-yellow-black

Cable core is wrapped with a PET

or PP foil (overlap > 15%)

< 80 mm Laylength

4. Outer shield

Shield Beldfoil®)

Shield Material Aluminium / Polyester tape

Shield Thickness Alu 9 µm 100% Shield coverage

Drainwire 0.4 mm Solid tinned Cu

4. Sheath

FRNC (like RAL 6017) Material

Colour Green Nominal thickness 1.4 mm

6.3 mm +/- 0.3 mm Nominal diameter

Cable has a round appearance, sheath easy to remove.

| SENDING A | I THE DIGHT SIGNALS | |
|-------------------------------|---------------------|--|
| SENDING ALL THE RIGHT SIGNALS | | |

| TECHNICAL DATA SHEET | code | YE00906 |
|-----------------------------|---------|------------|
| | version | 2 |
| EIB cable 4x0.8B PE FS FRNC | date | 2009-03-10 |
| | page | 2/2 |

REQUIREMENTS AND TEST METHODS

Electrical:

Maximum resistance conductor34 Ω/kmMaximum capacitance conductor-conductor100 nF/km

Testvoltage conductor-conductor 1000 VDC, 1 min. Testvoltage conductor-screen 1000 VDC, 1 min.

Mechanical and physical:

Flame resistance IEC 60332-1 Temperature range processing and operating -20 to +70 °C Temperature range storage -30 to +70 °C

Halogen content according to IEC754-1 zero

Corrosivity of fire gasses according to IEC754-2

Conductivity $\leq 100 \,\mu\text{S/cm}$ pH value ≥ 3.5

Minimum bending/setting radius 5*D/10

Cableprint: (in black ink) once every meter.

(WW/YY week and year nr of production, xxxx M = metermarking)

"BELDEN (TM) YE00906 EIB 2X2X0.8 MM WW/YY xxxx M REG NR. 109/7254/05"





| TECHNICAL DATA SHEET | code | YE00906 |
|-----------------------------|---------|------------|
| | version | 2 |
| EIB cable 4x0.8B PE FS FRNC | date | 2009-03-10 |
| | page | 3/2 |

Belden CDT believes this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.