



Applications:
U.T.P. – Unshielded Twisted Pairs cables cat. 5e UL/ETL verified for Local Area Network – LAN cables.

tasker® C704 for fixed installations and **tasker® C705** for assembled cables or mobile installations.
For **RJ 45 8 Pin** connectors.
Standards: **EIA/TIA 568**.

Characteristics:

Conductors: **C704:** stiff wire in O.F.C. red copper
C705: stranded in O.F.C. red copper
Cond. insulation: PE
Pair colours: White/blue-Blue, White/orange-Orange, White/green-Green, White/brown-Brown
transparent Polyester (Pet)
External Sheath: PVC
Sheath colour: Grey



| tasker® Code | Cond. number | Nominal section AWG | Cond. Format. mm. | External Core Ø mm. | External Inner Sheath Ø mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|---------------------------------------|----------------------|------------------------|--------------------------------|--------------------------------|------------------------------|------|-----|
| | | | | | | | mt. | Type | Kg. |
| C704 | 4x2 | 4 x 2 x 24 (0,22 mm ²) | 1x0,51 | 0,9 | | 6,0 | 100 | B | 3,6 |
| | | | 7x0,15 | | | 0,9 | 6,0 | 300 | B |
| C705 | 4x2 | 4 x 2 x 26 (0,14 mm ²) | 1x0,51 | 0,9 | | 6,0 | 100 | B | 3,5 |
| | | | 7x0,15 | | | 0,9 | 6,0 | 300 | B |

| Conductor Resistance Ω/Km ± 5% | Impedance Ω ± 5% 1 ÷ 100 MHz | Max Rated Voltage AC - V |
|-----------------------------------|------------------------------------|---------------------------------------|
| 90 | 100 | 49 |
| 140 | 100 | 49 |
| | | Operative Temperature °C -15 / +70 |



Applications:
F.T.P. - Foiled Twisted Pairs cable cat. 5e UL/ETL verified for Local Area Network – LAN cables.
For **RJ 45 8 Pin shielded** connectors
Standards: **EIA/TIA 568**.

Characteristics:

Conductors: stiff wire in O.F.C. red copper
Cond. insulation: PE
Pair colours: White/blue-Blue, White/orange-Orange, White/green-Green, White/brown-Brown
Aluminium tape covering 100%
Drain wire: stranded in tinned copper
External Sheath: PVC
Sheath colour: Grey



| tasker® Code | Cond. number | Nominal section AWG | Cond. Format. mm. | External Core Ø mm. | External Inner Sheath Ø mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) | | |
|--------------|--------------|---------------------------------------|----------------------|------------------------|--------------------------------|--------------------------------|------------------------------|------|-----|
| | | | | | | | mt. | Type | Kg. |
| C706 | 4x2 | 4 x 2 x 24 (0,22 mm ²) | 1x0,51 | 0,9 | | 7,0 | 100 | B | 3,7 |
| | | | | | | | 7,0 | 300 | B |

| Conductor Resistance Ω/Km ± 5% | Impedance Ω ± 5% 1 ÷ 100 MHz | Max Rated Voltage AC - V |
|-----------------------------------|------------------------------------|---------------------------------------|
| 90 | 100 | 49 |
| | | Operative Temperature °C -15 / +70 |