



			Wymiary czołowe 18 x 18 mm	Wymiary czołowe 25 x 25 mm	
Działanie:	Kolor	Typ	Typ		Opak.
		Nr artykułu	Nr artykułu		

Napędy przełączników podświetlanych, IP65


Z ogranicznikiem obrotu VS

bez żarówki
3 położenia

	45° ↙ ↘ 45°	○	Q18LWK3-WS 072322	Q25LWK3-WS 072358	5 szt.
	45° ↙ ↘ 45°	●	Q18LWK3-RT 072323	Q25LWK3-RT 072359	
	45° ↙ ↘ 45°	●	Q18LWK3-GN 072324	Q25LWK3-GN 072360	
	45° ↘ ↙ 45°	○	Q18LWK3R-WS 072325	Q25LWK3R-WS 072361	
	45° ↘ ↙ 45°	●	Q18LWK3R-RT 072326	Q25LWK3R-RT 072362	
	45° ↘ ↙ 45°	●	Q18LWK3R-GN 072327	Q25LWK3R-GN 072363	
	45° ↙ ↘ 45°	○	Q18LWK3R1-WS 072328	Q25LWK3R1-WS 072364	
	45° ↙ ↘ 45°	●	Q18LWK3R1-RT 072329	Q25LWK3R1-RT 072365	
	45° ↙ ↘ 45°	●	Q18LWK3R1-GN 072330	Q25LWK3R1-GN 072366	
	45° ↙ ↘ 45°	○	Q18LWK3R2-WS 072331	Q25LWK3R2-WS 072367	
	45° ↙ ↘ 45°	●	Q18LWK3R2-RT 072332	Q25LWK3R2-RT 072368	
	45° ↙ ↘ 45°	●	Q18LWK3R2-GN 072333	Q25LWK3R2-GN 072369	

Z żarówką
3 położenia

	45° ↙ ↘ 45°	○	Q18LWK3-WS/WB 072334	Q25LWK3-WS/WB 072346	5 szt.
	45° ↙ ↘ 45°	●	Q18LWK3-RT/WB 072335	Q25LWK3-RT/WB 072347	
	45° ↙ ↘ 45°	●	Q18LWK3-GN/WB 072336	Q25LWK3-GN/WB 072348	
	45° ↘ ↙ 45°	○	Q18LWK3R-WS/WB 072337	Q25LWK3R-WS/WB 072349	
	45° ↘ ↙ 45°	●	Q18LWK3R-RT/WB 072338	Q25LWK3R-RT/WB 072350	
	45° ↘ ↙ 45°	●	Q18LWK3R-GN/WB 072339	Q25LWK3R-GN/WB 072351	
	45° ↙ ↘ 45°	○	Q18LWK3R1-WS/WB 072340	Q25LWK3R1-WS/WB 072352	
	45° ↙ ↘ 45°	●	Q18LWK3R1-RT/WB 072341	Q25LWK3R1-RT/WB 072353	
	45° ↙ ↘ 45°	●	Q18LWK3R1-GN/WB 072342	Q25LWK3R1-GN/WB 072354	
	45° ↙ ↘ 45°	○	Q18LWK3R2-WS/WB 072343	Q25LWK3R2-WS/WB 072355	
	45° ↙ ↘ 45°	●	Q18LWK3R2-RT/WB 072344	Q25LWK3R2-RT/WB 072356	
	45° ↙ ↘ 45°	●	Q18LWK3R2-GN/WB 072345	Q25LWK3R2-GN/WB 072357	



Wyposażenie dodatkowe

Wyposażenie ułatwiające montaż i wyposażenie dodatkowe → Strona 2/81

Elementy stykowe

styki zwierne → Strona 2/70

styki rozwierne → Strona 2/70