

TECHNICAL DATA

Scapa 003

Rayon Cloth Adhesive Tape

DESCRIPTION

Scapa 003 is a rayon cloth tape, single coated with a thermosetting rubber based adhesive. Scapa 003 is available in black.

APPLICATIONS

- Wrapping of automotive electrical wiring harnesses
- Hand application
- Product designed for applications which require a good temperature resistance, class T2 (105°C)

PRODUCT BENEFITS

- Easy tear by hand
- Smooth and controlled unwind .
- Anti-squeak properties
- Self-extinguishing on harness
- Halogen free
- Lead free
- Conforms to European Directive 2000/53/EC for End of Vehicle Life (ELV) recycling (does not contain heavy metals)
- Operating temperature between -30°C to +105°C

Page 1 of 2

003.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer

TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
Thickness	mm	0.25	AFERA 4006
Tensile Strength	N/cm	65	AFERA 4004
Elongation at Break	%	8	AFERA 4005
Peel Adhesion to Backing	N/cm	2.0	AFERA 4001
Thermal Class	°C	105 – T2	RENAULT/PSA
Flame Resistance	Туре	В –	RENAULT
		Self-extinguishing	D45 1333

STANDARD PRESENTATION

- Roll length: 15, 25 and 50 metres
- Roll width: 15, 19, 25mm in 15m 9, 15, 19, 25mm in 25m 9 to 300mm in 50m
- Core:

- 38mm Scapa branded cardboard core and 76mm neutral cardboard core
- Packaging: Cardboard bulk packed using interleaving sheet between layers
- Colours:
- Cardboard Black

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +5°C and +25°C. A strict use-by date of 6 months from the date of manufacture is recommended.

The tape should be applied with sufficient pressure to ensure an optimum bonding and prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Issue: 5

Page 2 of 2

003.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, it shall not, it shall not, it shall not, its shall not extinctly arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.